Aqualem R





A unique water-based cleaning formulation designed for use on most water-based paints, dyes and inks used in the litho and offset printing industries.

Aqualem R has cleaning power equal to traditional ink cleaners.

Water dilutable

- Biodegradable
- Non-flammable

DILTECHNICS

WHERE TO USE

• Suitable for cleaning most water-based paints, dyes and inks used in the printing industry.

HOW TO USE

For heavily soiled components

- Use as supplied.
- Soak items for 10 minutes and wash off with clean water.

For general cleaning

- Dilute with water at 2-10% (1:98 to 1:9), depending on level of soiling.
- Apply by brush, spray or by dipping.
- Rinse after use.

PHYSICAL PROPERTIES

Appearance	Yellow liquid
Specific gravity	1.020
рН	~11.0
Flash point (°C)	62
VOC content	<10% (3.5% natural origin)

TRANSPORT INFORMATION

UN Number: 3082 Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.. Hazard Class: 9 Packing group: III Environmental hazard: Marine pollutant

DISPOSAL

Do not release to the environment. Dispose of excess product according to your local regulations. Containers should be rinsed before recycling.

STORAGE AND SHELF LIFE

Store locked up. Best stored as supplied in original, unopened containers, off the ground and out of direct sunlight.

Do not expose to temperature extremes and prevent contamination from foreign materials. Shelf life: 4 years from Date of Manufacture. For further guidance on handling and storage, see Safety Data Sheet.

TECHNICAL SERVICES & SALES SUPPORT

For our UK customers, our products are available 24/7 via our 24 hour emergency call out service: +44 (0) 1561 361515.

Oil Technics Ltd manufacture in Scotland under ISO 9001:2015 and ISO 14001: 2015 accredited management systems.

PACK SIZES

- 4 x 5 Litre containers 200 litre drums
- 20 litre containers
- 1000 litre IBCs



Oil Technics Ltd

Linton Business Park, Gourdon, Aberdeenshire, Scotland UK DD10 0NH | +44 (0) 1561 361515 | info@oiltechnics.com | oiltechnics.com











Oil Technics Ltd reserve the right to modify any specification at any time and without prior notice.

Rev1122