

Lemsolv CX1



Solvent Cleaner - QC marking, Fingerprints & Sealants



A water rinsable citrus based solvent precision cleaner for the removal of fingerprints and QC markings on pre-inspection precision components.

Formulated from oxygenated solvents and orange oils, Lemsolv CX1 is also very effective at removing cured and semi cured adhesives and sealants. Designed to replace hazardous products such as MEK and Methylene Chloride.

- Precision cleaner
- Water rinsable
- Dries film free
- 61°C Flash Point

HOW TO USE

- Use as required in immersion, spray or bench top cleaning applications.
- May soften some soft bitumen or rubber sealants: test before application or call our Technical Department for further information.

PHYSICAL PROPERTIES

Appearance	Pale straw liquid
Specific gravity	0.95
pH	~7.0
Flash point (°C)	>61
Vapour Pressure @ 25°C (mmHg)	<5
VOC content	54% (<5% natural origin)

TRANSPORT INFORMATION

UN Number: 3082
Proper shipping name:
ENVIRONMENTALLY HAZARDOUS SUBSTANCE,
LIQUID, N.O.S.
Hazard Class: 9 Packing group: III
Environmental hazard: Marine pollutant

DISPOSAL

Dispose of excess product according to your local regulations. Containers should be rinsed before recycling.

STORAGE AND SHELF LIFE

Store locked up. Best stored as supplied in original, unopened containers, off the ground and out of direct sunlight. Do not expose to temperature extremes and prevent contamination from foreign materials. Shelf life: 4 years from Date of Manufacture. For further guidance on handling and storage, see Safety Data Sheet.

TECHNICAL SERVICES & SALES SUPPORT

For our UK customers, our products are available 24/7 via our 24 hour emergency call out service: +44 (0) 1561 361515. Oil Technics Ltd manufacture in Scotland under ISO 9001:2015 and ISO 14001: 2015 accredited management systems.

PACK SIZES

- 4 x 5 Litre containers
- 20 litre containers
- 200 litre drums
- 1000 litre IBCs
- 12 x 500ml trigger sprays



Oil Technics Ltd

Linton Business Park, Gourdon, Aberdeenshire, Scotland UK DD10 0NH | +44 (0) 1561 361515 | info@oiltechnics.com | oiltechnics.com

