Lemsolv CX4

Solvent Cleaner - Sealants, Resins & Barcode Overprinting Ink



A precision solvent for the removal of sealants, inks, uncured and partly cured resin and barcode over-printing ink.

Formulated from oxygenated solvents and orange oils, Lemsolv CX4 is designed to replace hazardous products such as MEK and Methylene Chloride.

- Precision cleaner Fast drying Film free
- Aerospace approved meets Westland Helicopter Ref. IL48

HOW TO USE

- Suitable for use by spray, wipe or immersion cleaning in removing surface adhesive and sealants.
- Also available in trigger sprays and wipes for benchtop cleaning applications.
- May soften soft bitumen and rubber solvents: test before application or call our Technical Department for further information.

PHYSICAL PROPERTIES

Pale yellow liquid
0.89
TBC
>42
5°C (mBar) <5
100% (<5% natural origin)

TRANSPORT INFORMATION

UN Number: 3271 Proper shipping name: ETHERS, N.O.S. Hazard Class: 3 Packing group: III Environmental hazard: Marine pollutant; Hazardous to the environment

DISPOSAL

Dispose of excess product according to your local regulations. Containers should be rinsed before recycling.

Acrylic safe

LTECHNICS

STORAGE AND SHELF LIFE

Store locked up. Best stored as supplied in original, unopened containers, off the ground and out of direct sunlight.

Do not expose to temperature extremes and prevent contamination from foreign materials. Shelf life: 4 years from Date of Manufacture. For further guidance on handling and storage, see Safety Data Sheet.

TECHNICAL SERVICES & SALES SUPPORT

For our UK customers, our products are available 24/7 via our 24 hour emergency call out service: +44 (0) 1561 361515.

Oil Technics Ltd manufacture in Scotland under ISO 9001:2015 and ISO 14001: 2015 accredited management systems.

PACK SIZES

- 4 x 5 Litre containers
 200 litre drums
- 20 litre containers1000 litre IBCs
- Tins of 250 wipes (200 x 200mm)
- 12 x 500ml trigger sprays



Oil Technics Ltd

Linton Business Park, Gourdon, Aberdeenshire, Scotland UK DD10 0NH +44 (0) 1561 361515 info@oiltechnics.com oiltechnics.com













Rev0123