Powerwash SF



Synthetic Flux Solvent Cleaner



Powerwash SF removes most types of synthetic and noclean fluxes and residue as well as some resin-based types effectively.

Compatible with jigs, tools, fixtures and track components, Powerwash SF dries quickly to maintain short wash cycles and does not damage the adhesive mounting strip or screen surfaces.

- Quick drying
- Residue free
- Low toxicity

- Mild odour
- Flash point of 42°C

WHERE TO USE

- A solvent cleaner designed to remove synthetic and no-clean flux pastes and residues.
- Also suitable for use on some resin-based fluxes.
- Compatible with jigs, tools, fixtures and track components.

HOW TO USE

• Use as required in immersion, spray, ultrasonic or bench top cleaning.

PHYSICAL PROPERTIES

 Appearance 	Colourless liquid
 Specific gravity 	0.890
• pH	TBC
• Flash point (°C)	42
 VOC content 	100% (<5% natural origin)

ENVIRONMENTAL IMPACT

Biodegradable
 No bioccumulation potential

TRANSPORT INFORMATION

UN Number: 1993 Proper shipping name: FLAMMABLE LIQUID, N.O.S.

Hazard Class: 3 Packing group: III Environmental hazard: Marine pollutant

STORAGE AND SHELF LIFE

Store locked up. Best stored as supplied in original, unopened containers, off the ground and out of direct sunlight.

Do not expose to temperature extremes and prevent contamination from foreign materials. Shelf life: 4 years from Date of Manufacture. For further guidance on handling and storage, see Safety Data Sheet.

DISPOSAL

Dispose of excess product according to your local regulations. Containers should be rinsed before recycling.

TECHNICAL SERVICES & SALES SUPPORT

For our UK customers, our products are available 24/7 via our 24 hour emergency call out service: +44 (0) 1561 361515.

Oil Technics Ltd manufacture in Scotland under ISO 9001:2015 and ISO 14001: 2015 accredited management systems.

PACK SIZES

- 4 x 5 Litre containers
- 20 litre containers
- 200 litre drums
- 1000 litre IBCs









Oil Technics Ltd

Linton Business Park, Gourdon, Aberdeenshire, Scotland UK DD10 0NH | +44 (0) 1561 361515 | info@oiltechnics.com | oiltechnics.com











