

Lemsolv Industrial



Heavy Duty, Water Rinsable Degreasing Solvent



A highly efficient heavy duty solvent degreaser, Lemsolv Industrial removes the most tenacious grease, heavy oil, wax, asphaltines and bitumen emulsions.

A blend of biodegradable surfactants and performance enhancing solvents, Lemsolv Industrial has a very high solvency factor (>100Kb), enabling it to penetrate and lift even the heaviest of oil contamination quickly and safely.

- Free from D-limonene, chlorine and other hazardous solvents
- High solvency
- High flash point (65°C)
- Non-flammable
- Biodegradable
- Water rinsable
- Separator friendly

WHERE TO USE

Lemsolv Industrial removes heavy oil, wax, grease, asphaltines and bitumen emulsions up to 10 times faster than traditional solvents from cleaning oil storage tanks and equipment.

Extensively used throughout the engineering and transport industry for cleaning and degreasing for:

- Heavy plants
- Oil tanks
- Machinery
- Workshop floors
- Engines
- Chains
- and many other applications...

HOW TO USE

- Use by contact, dip, immersion, brush or spray.
- Apply undiluted to the oil contaminated area and allow a contact time of 10–15 minutes before rinsing with water.
- Allow up to 60 minutes when used in the cleaning of oil tanks or heater tubes.
- For best results use hot water to rinse clean.
- Transfer oily water residue to slop tank for treatment.

PHYSICAL PROPERTIES

• Appearance	Clear colourless liquid
• Specific gravity	0.900
• pH	~6.5
• Flash point (°C)	65
• VOC content	<20%

ENVIRONMENTAL IMPACT

- Biodegradable
- No bioaccumulation potential

STORAGE AND SHELF LIFE

Best stored as supplied in original, unopened containers off the ground and out of direct sunlight.

Do not expose to temperature extremes and prevent contamination from foreign materials.

Shelf life: 4 years from Date of Manufacture.

For further guidance on handling and storage, see Safety Data Sheet.

DISPOSAL

Avoid release to the environment. Dispose of excess product according to your local regulations. Containers should be rinsed before recycling.

TECHNICAL SERVICES AND SALES SUPPORT

For our UK customers, our products are available 24/7 via our 24 hour emergency call out service: +44 (0) 1561 361515.


Oil Technics Ltd manufacture in Scotland under ISO 9001: 2015 and ISO 14001: 2015 accredited management systems.

PACK SIZES

- 4 x 5 Litre containers
- 20 litre containers
- 200 litre drums
- 1000 litre IBCs
- Tubs of 290 wipes (170 x 280mm)
- 12 x 500ml trigger sprays



Lemsolv Industrial spot testing



Oil Technics Ltd

Linton Business Park, Gourdon, Aberdeenshire, Scotland UK DD10 0NH | +44 (0) 1561 361515 | info@oiltechnics.com | oiltechnics.com



Oil Technics Ltd reserve the right to modify any specification at any time and without prior notice.